
FACTA B

RECESSED FOR BLOCK INFILL


UTILITY PRODUCTS TD

Specification Info:

- Recessed cover for block infill.
- Plain seated (Unsealed) – Unlocked.
- Heavy duty corner lifting points.
- 100mm tray depth.
- Plain internal tray for bedding and block infill.
- Galvanised and certified to BS EN ISO 1461.







A	B	C	D	E	Code
300 x 300mm	370 x 370mm	470 x 370mm	100mm	108mm	378677
450 x 450mm	520 x 520mm	620 x 590mm	100mm	108mm	378678
600 x 450mm	670 x 520mm	670 x 620mm	100mm	108mm	378679
600 x 600mm	670 x 670mm	770 x 670mm	100mm	108mm	378680
675 x 675mm	745 x 745mm	845 x 745mm	100mm	108mm	376575
750 X 600mm	820 x 670mm	820 x 770mm	100mm	108mm	378681
750 x 750mm	820 x 820mm	920 x 820mm	100mm	108mm	376424
900 x 600mm	970 x 670mm	970 x 770mm	100mm	108mm	376448

Loading:

FACTA B:

- 5 tonne slow moving wheel load.
- 25tonne gross laden vehicle weight.

PN - Steel equivalent loadings to BS EN 124 but for slow moving areas of 20mph or less.

Accessories:

- Heavy duty short handle lifting key (Each) Code (379206)
- Heavy duty long handle lifting key (Each) Code (379207)
- M12 through bolts for frame fixing (4no) Code (379211)

Infill:

As standard the cover can take all infills:

- Sand and cement bedding and a maximum block depth of 80mm.
- Bedding and solid infills like tactile paving, granite sets, concrete slabs etc.
- Sand and cement bedding and a final tarmac finish.

Fitting:

- Unit must be fitted with cover in the frame.
- Minimum 25mm rapid set bedding mortar recommended.
- Additional concrete surround of 30mm covering in building in lugs.
- Alternatively, the frame can be bolted down through the 13mm holes in the lugs. Fixings not provided – see accessories.

Access:

- Cover to be lifted using heavy duty lifting keys via corner lifting points.
- 4no lifting keys required for two-person lift-out.

Maintenance:

- 6-month maintenance recommended.
- Removal of cover and light brush to clean debris from frame seating.

Special Options:

- Single EPDM rubber sealed (Unlocked).
- Double EPDM rubber sealed (Locked).
- Triple sealed – double sealed and locked, c/w additional inner sealing plate (Airtight and water resistant).
- Allen head screw locking.
- Security screw locking (Torx-pin).
- Any tray/overall depth required. (Some standard depths - 60mm, 80mm, 120mm and 150mm).
- Square to round, Circular opening to suit PPIC.
- Fully stainless (Grade 304).
- Fully stainless (Grade 316).

TD THOMAS | DUDLEY

Thomas Dudley Utility Products
295 Birmingham New Road, Dudley, West Midlands, DY1 4SJ
0121 521 2503
utilitysales@thomasdudley.co.uk
www.tdfoundry.co.uk

UTILITY PRODUCTS TD